



Brake For Altitude Drive

No.	Qty.	Description
48	4	1/2-13x1.5 socket-head cap screw (stainless)
47	4	1/2-13x3 socket-head cap screw (stainless)
46	4	Nut for 1/2-13 bolt (stainless)
45	2	1/2-13x3 socket-head cap screw (stainless)
44	2	1/2-13xB socket-head cap screw (stainless)
43	6	3/8-16x2.5 socket-head cap screw (stainless)
42	2	Front Mount for Shock Absorber (no. 2)
41	2	Rear Mount for Shock Absorber (no. 2)
40	2	Altitudg Brake Striker (no. 2)
38	16	Lock washer for 5/16 screw (stainless)
37	16	Washer for 5/16 screw (stainless)
36	16	5/16-18x1.5 socket-head cap screw (stainless)
35	6	Nut for 1/2-13 bolt (stainless)
34	6	1/2-13x2 socket-head cap screw (stainless)
33	4	Shock Absorber (See Contr. A3/4x3-S; prov. by TSU)
32	2	Front Mount for Shock Absorber (no. 1)
31	2	Rear Mount for Shock Absorber (no. 1)
30	2	Altitudg Brake Striker (no. 1)

Tenn. State Univ.
 CASS 2-m AST Project
 07/07/97
 J.A.E. AST-09-A03